

Wheels Tyres and Brakes

1. Brake pipes must run through the driver's compartment
2. Efficient brakes must be on all wheels at all times.
3. Hand/ parking brake is optional.
4. Cars must not have more than four wheels.
5. All wheel nuts must be steel and in thread contact over a minimum length of 1 ½ time's bolt/stud diameter.
6. Tyres marked in any way for road racing or competition use, or not for highway use are not permitted for production groups A, B, Mod C and Juniors. With the exception that Yokohama AO21r tyres are permitted on all production groups.
7. Any ECE (Economic Commission for Europe) approved tyre within the size constraints for a said group is permitted in production groups A, B, Mod C and Juniors. The E mark will be in the form of a circle or rectangle containing the letter "E" or "e" followed by a number. A large letter "E" indicates ECE type approval. A small letter "e" indicates compliance with EEC Directive 92/23/EEC.
8. E Marks must be visible, remoulds are permitted.
9. Any tyre that a competitor is not sure is suitable for use should check with SEGTO Committee before using the tyre in question.
10. Safety wheel nuts to prevent wheels pulling off over standard nut are recommended.
11. Wheel Spacers are not permitted for production groups A, B, Mod C and Juniors
12. Wheel Spacers are permitted on 1450, Super Saloons and Specials and must not exceed 1" (25mm) thickness.
13. Multiple or laminated spacers prohibited.
14. Brakes are free on 1450, Super Saloons and Specials.
15. Brakes are free within the manufacturer's model range on Juniors, Prod A, B, & Mod C.
16. Adjustable bias brake valves are permitted on 1450, Super Saloons and Specials
17. Adjustable bias brake valves are not permitted on Juniors, Prod A, B, & Mod C.
18. All groups can use alloy wheels provided correct wheel nuts and studs/bolts are used.
19. Wheel diameters are free but must not exceed 6" wide on Juniors, Prod A, Prod B & Mod C.
20. Maximum tyre size is 175mm wide on Juniors and Prod A.
21. Maximum tyre size is 185mm wide Prod B & Mod C.
22. The SEGTO technical committee reserve the right to review tyre regulations as they develop.
23. Tyre outside edge must remain within the confines of the bodywork on all saloons, hatchbacks and pickups
24. Tubed tyres are recommended.
25. No more than two wheels to be fitted to one axle.
26. All cars must retain same diameter wheels on same axle.
27. No stud or chained tyres permitted.
28. Sidewall gaiters are not permitted.